QUICK REFERENCE GUIDE > RS6019S2R1 Date: 25.11.2025 > 1

60cm Series 9 Integrated Dual Zone Refrigerator

Integrated




Pair with the Integrated Dual Zone Freezer for the ultimate kitchen solution – this model features two independent food zones taking cooling flexibility to a new level.

- Flush fit design with 4mm gaps and custom height installation
- Two independent food zones with adjustable temperature from 1 to 6°C
- Customise with your own kitchen cabinetry or purchase our stainless steel door panel accessory
- · Easy-to-use touch-control panel and Wi-Fi capability

DIMENSIONS

Height 1870 mm
Width 592 mm
Depth 576 mm



FEATURES & BENEFITS

Perfect Fit

These models fit flush, with only 4mm gaps around them and no visible hinges or grilles. Our Integrated models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

Independent Food Zones

When it comes to optimal food preservation, one temperature does not fit all. With two independent food zones, you can create the perfect climate for storing different foods. Each zone has adjustable temperature from 1°C to 6°C, ideal for items such as fruit and vegetables, dairy products, meats and leftovers.

Mix & Match

These modular refrigerators and freezers can be mixed and matched, with different sizes and finishes. Installed side by side or individually throughout the kitchen, you can create a cooling solution to suit your lifestyle. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

Clever Energy

ActiveSmart™ Foodcare learns how you live. It is technology that understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

Flexible Storage

Designed to make it simple for you to store, access and remove food, this refrigerator includes LED-lit adjustable cantilevered shelving and full extension veggie bins.

Simple Installation

Our Integrated products are easy to install, whether you are renovating your kitchen or designing a new one. Adjustable front and rear feet allow for uneven floors alongside adjustable door panels that can be customised to match your kitchen. These models are designed to easily slide into place as separate units – a perfect fit for European design kitchens.

Ease Of Use

Using the intuitive touch-sensitive control panel, you can easily adjust the temperature to suit. Beautiful to use, the refrigerator door is family safe with a soft-close mechanism.

SPECIFICATIONS

		Adjustable door shelves	4	Product dimensions
Accessories (included)		Adjustable glass cantilevered shelves	•	Depth 576 mm
Hinge change (from right hinge to left	•	Covered door shelves	1	Height 1870 mm
hinge)		Door alarm	•	Width 592 mm
		LED ceiling lighting	•	
		SmartTouch control panel	•	
Accessories (sold separately)		Stackable bottle holders	2	
Door panel set stainless steel	Right & Left hinge RD6019			SKU 26211
Handle kit Classic	AHCLRDSF	Installation Dimensions		
Handle kit Contemporary round, aluminium	AHSRDSF	Minimum inside width of cabinetry frame	600 mm	The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these
Handle kit Contemporary square fine, aluminium	AHD5RDSF	Minimum internal depth of cabinetry	600 mm	dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page
Handle kit Contemporary square fine, black	AHD5RDSFB	Minimum internal height of cabinetry	1880 mm	correctly describes the model currently available. $\ensuremath{\texttt{@}}$ Fisher & Paykel
Joiner kit	AJRS19LR			Appliances Ltd 2020
Toe kick stainless steel 1200mm	AKRS12010			
Toe kick stainless steel 1800mm	AKRS18010	Performance		Other product downloads available at fisherpaykel.com
Toe kick stainless steel 600mm	AKRS06010	ActiveSmart™ Foodcare	•	
		Adaptive defrost	•	↓ DWG
		Dual evaporator	•	± DWG
Capacity		Frost free	•	
Total gross capacity	338 L	Humidity control system	•	→ DXF Appliance with K08 Hinge
Volume	314 L	Humidity controlled crisper bins	2	<u>↓</u> DXF
Volume refrigerator	314 L	Inverter controlled compressor	•	
		Sabbath mode	•	DXF Appliance with Panel Preparation→ Archicad
Computation				→ Declaration of Conformity (Chinese)
Consumption		Power requirements		± Energy Label (Chinese)
Energy rating	Grade 1	Power requirements		
Energy usage	0.27kWh/24h	Rated current	10 A	
		Supply frequency	50 Hz	→ Planning Guide (English)
		Supply voltage	230 V	
Features				<u>↓</u> Revit
				<u>↓</u> Rhino

QUICK REFERENCE GUIDE > RS6019S2R1 Date: 25.11.2025 > 3

- ↓ Rhino Appliance with Custom Panel
- ↓ Rhino Appliance with Door and Classic Round Handle
- ↓ Rhino Appliance with Door and Contemporary Round Handle
- Rhino Appliance with Door and Professional Round Flush Handle
- Rhino Appliance with Door and Square Fine Black Handle
- ↓ Rhino Appliance with Door and Square Fine Handle
- ↓ SketchUp
- ↓ SketchUp Appliance with Custom Panel
- ↓ SketchUp Appliance with Door and Classic Round Handle
- ↓ SketchUp Appliance with Door and Contemporary Round Handle
- SketchUp Appliance with Door and Professional Round Flush Handle
- ↓ SketchUp Appliance with Door and Square Fine Black Handle
- ↓ SketchUp Appliance with Door and Square Fine Handle
- ↓ User Guide (English)
- ↓ User Guide (Chinese)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.