QUICK REFERENCE GUIDE > DD60SHTI9

Integrated Single DishDrawer Dishwasher, Tall

Series 9 | Integrated

Panel Ready



Integrating into your kitchen design seamlessly, with extra height for larger dishes in the tall top drawer.

- With extra height for taller dishes, and customisable internal shelving
- · Knock to pause function is perfect if you miss a dish
- Quick wash, Sanitise and Extra Dry options provide superior performance


 Customise with your own front panel and handle to match your kitchen cabinetry, or choose our stainless steel panel

DIMENSIONS

Height 454 mm

Width 599 mm

Depth 553 mm



FEATURES & BENEFITS

SPECIFICATIONS

Accessories (included)

Cutlery basket

Knife clip and multipurpose clip

Accessories (sold separately)

Door panel black stainless steel	ADDD60STPB
Door panel recessed handle black stainless steel	ADDD60STNB
Door panel recessed handle matte black glass	ADDD60STZB
Door panel recessed handle stainless steel	ADDD60STNX
Door panel stainless steel	ADDD60STPX
Handle kit Contemporary square fine, aluminium	AHD5DDDW60S
Handle kit Contemporary square fine, black	AHD5DDDW60B

Capacity and loading

Omm
•
•
•
8

Consumption

Cleaning Index	1.16
Drying Index	0.97
Energy consumption	0.61kWh/cycle
Water consumption	8L

QUICK REFERENCE GUIDE > DD60SHTI9

Controls		Depth	553 mm
Electronic fault/Diagnostic indicator	•	Height	454 mm
End of cycle beeps	•	Width	599 mm
Energy saving delay start option of up to 12 hours	•		
Internal wash selector	•	Wash Program Modifiers	
Keylock	•	Extra Dry	•
Knock to pause	•	Quick	•
Rinse aid indicator light	•	Sanitise	•
		Wash modifiers	3
Features			
Built-in water softener	•	Wash Programs	
Fan assisted drying	•	Delicate	•
Flood protection	•	Eco	•
Flow through detergent dispenser	•	Fast	•
Motor type	BLDC	Heavy	•
Quiet operation	•	Medium	•
SmartDrive™ technology	•	Rinse	•
		Wash programs	6
Performance			
Noise emissions	43 dBA	Water connection	
		Water pressure	100kPa - 1000kPa
Power requirements		Water supply	3/4" BSP (20mm) Connector Water Inlet Hose
Amperage	5A		miet nose
Supply frequency	50Hz		
Supply voltage	220 - 240V		
		SKU	81246

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

↓ 2D-DXF DishDrawer[™] Dishwasher

Quick Start Guide MMMM ZH

Revit Integrated Single DishDrawer $^{\text{\tiny{IM}}}$ Dishwasher

Rhino Integrated Single DishDrawer™ Dishwasher

Rhino Integrated Single DishDrawer™ Dishwasher with Door Panel and Contemporary Square Handle

Sketchup Integrated Single DishDrawer™ Dishwasher

Sketchup Integrated Single DishDrawer™ Dishwasher with Door Panel and Contemporary Square Handle



Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Product dimensions