QUICK REFERENCE GUIDE > RS6019S2R1 Date: 02.04.2025 > 1

60cm Series 9 Integrated Dual Zone Refrigerator

Series 9 | Integrated

Panel Ready | Right Hinge




Pair with the Integrated Dual Zone Freezer for the ultimate kitchen solution – this model features two independent food zones taking cooling flexibility to a new level.

- Flush fit design with 4mm gaps and custom height installation
- Two independent food zones with adjustable temperature from 1 to 6°C
- Customise with your own kitchen cabinetry or purchase our stainless steel door panel accessory

Easy-to-use touch-control panel and Wi-Fi capability

DIMENSIONS

Height 1870 mm
Width 592 mm
Depth 576 mm



FEATURES & BENEFITS

Perfect Fit

These models fit flush, with only 4mm gaps around them and no visible hinges or grilles. Our Integrated models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

Independent Food Zones

When it comes to optimal food preservation, one temperature does not fit all. With two independent food zones, you can create the perfect climate for storing different foods. Each zone has adjustable temperature from 1°C to 6°C, ideal for items such as fruit and vegetables, dairy products, meats and leftovers.

Mix & Match

These modular refrigerators and freezers can be mixed and matched, with different sizes and finishes. Installed side by side or individually throughout the kitchen, you can create a cooling solution to suit your lifestyle. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

Clever Energy

ActiveSmart™ Foodcare learns how you live. It is technology that understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

Flexible Storage

Designed to make it simple for you to store, access and remove food, this refrigerator includes LED-lit adjustable cantilevered shelving and full extension veggie bins.

Simple Installation

Our Integrated products are easy to install, whether you are renovating your kitchen or designing a new one. Adjustable front and rear feet allow for uneven floors alongside adjustable door panels that can be customised to match your kitchen. These models are designed to easily slide into place as separate units – a perfect fit for European design kitchens.

Ease Of Use

Using the intuitive touch-sensitive control panel, you can easily adjust the temperature to suit. Beautiful to use, the refrigerator door is family safe with a soft-close mechanism.

SPECIFICATIONS

QUICK REFERENCE GUIDE > RS6019S2R1 Date: 02.04.2025 > 2

		Adjustable glass cantilevered shelves	•	Depth	576 mm	
Accessories (included)		Covered door shelves	1	Height	1870 mm	
Hinge change (from right hinge to left hinge)	•	Door alarm	•	Width	592 mm	
		LED ceiling lighting	•			
		SmartTouch control panel	•			
		Stackable bottle holders	2	Warranty		
Accessories (sold separately)				Parts and labour	2 years	
Door panel set stainless steel	Right & Left hinge RD6019	Installation Dimensions		Sealed system parts only	5 years	
Handle kit Classic	AHCLRDSF	Minimum inside width of cabinetry frame	600 mm			
Handle kit Contemporary round, aluminium	AHSRDSF	Minimum internal depth of cabinetry	600 mm			
Handle kit Contemporary square fine, aluminium	AHD5RDSF	Minimum internal height of cabinetry	1880 mm	SKU	26211	
Handle kit Contemporary square fine, black	AHD5RDSFB					
Joiner kit	AJRS19LR			The product dimensions and specifications in this		
Toe kick stainless steel 1200mm	AKRS12010	Performance		product and model. Under our policy of continuou dimensions and specifications may change at any		
Toe kick stainless steel 1800mm	AKRS18010	ActiveSmart [™] Foodcare	•	check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020		
Toe kick stainless steel 600mm	AKRS06010	Adaptive defrost	•			
		Dual evaporator	•			
		Frost free	•			
Capacity		Humidity control system	•	Other product downloads available at fish	nerpaykel.com	
Total gross capacity	338 L	Humidity controlled crisper bins	2			
Volume	314 L	Inverter controlled compressor	•			
Volume refrigerator	314 L	Sabbath mode	•		and.	
				2D-DWG Refrigerator with Custom P2D-DXF Integrated Refrigeration - K0		
Consumption		Power requirements			-	
Energy usage	0.27kWh/24h	Amperage				
	•	Supply frequency	50 Hz	2D-DXF Integrated Refrigeration - Pa↓ Archicad 23 Refrigerator	ariei Preparation	
		Supply voltage	230 V	Declaration of Conformity ZH		
Features				↓ Energy Label ZH		
Adjustable door shelves	4			Service & Warranty Service & War		
,	·	Product dimensions		↓ Installation Guide EN		

QUICK REFERENCE GUIDE > RS6019S2R1 Date: 02.04.2025 > 3

- ↓ XXXXXXX ZH
- Planning Guide EN
- ↓ Planning Guide ZH
- ↓ Revit 18 Refrigerator
- ↓ Rhino 5 Refrigerator
- ↓ Rhino 5 Refrigerator with Custom Panel
- Rhino 5 Refrigerator Door with Classic Round Handle
- Rhino 5 Refrigerator Door with Contemporary Round Handle
- Rhino 5 Refrigerator Door with Professional Round Flush
 Handle
- ↓ Rhino 5 Refrigerator Door with Square Fine Black Handle
- Rhino 5 Refrigerator Door with Square Fine Handle
- Sketchup 8 Refrigerator
- ↓ Sketchup 8 Refrigerator with Custom Panel
- ↓ Sketchup 8 Refrigerator Door with Classic Round Handle
- Sketchup 8 Refrigerator Door with Professional Round Black Handle
- ↓ Sketchup 8 Refrigerator Door with Square Fine Black Handle
- ↓ Sketchup 8 Refrigerator Door with Classic Fine Handle

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.